

## DATA SHEET

**Product:** - PVC Coated Fabric 610gsm

### Application:

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	20X20 Inch
Yarn (DTEX)(DEN E ISO 2060)	1100*1100 D
Type of Coating	PVC coated on both side
Total Weight (DIN EN ISO 2286-2)	610g/m <sup>2</sup>
Width (DIN EN ISO 53354)	1.5M & 3M M
Tensile Strength (DIN 53354)	3000/2800 N/5CM
Tear Strength	300/280/N/5CM
Adhesion Strength	100N/5CM
Low Temperature-No Crack At	-30°C to + 70°C
Flame Retardant	B2/M2/NFPA701/B1/M1

### Features:

- A: Good adhesion
- B: Softness and Flexible
- C: Single side lac or both side Lac
- D: Color, weight can be customized
- E: Anti Mildew
- F: UV Protection
- G: Color Beige, off white, Gray



📍 50-CCA, Phase 6/C, DHA, Lahore-Pakistan.

🌐 [www.deltatentsintl.com](http://www.deltatentsintl.com)

✉ [info@deltatentsintl.com](mailto:info@deltatentsintl.com)

☎ +92 423 5730001 📞 +92 300 0444175